

FEATURES

- Busch or DVP oil recirculation pump 60 m³/h 50Hz;
- Vacuum level control using a high-precision absolute sensor that does not require calibration;
- Maximum achievable vacuum 99.8% (2 millibar);
- 613mm sealing bar (Standard) or 500mm short sealing bar (Optional), with double sealing. Easily removable for cleaning;
- Horizontal AISI304 vacuum chamber;
- 10 editable user programs;
- 1 cycle for vacuum containers;
- "H2Out" pump oil dehumidification cycle,
- Resettable oil change alarm;
- Menu accessible to technical assistance for parameter adjustment and reading of cycles carried out;
- Thickened PMMA cover with rounded edges. Automatic opening at the end of the cycle;
- Lid lowering system in resting position via lid lock;
- Easy maintenance access through chassis opening;
- PE filters for product positioning and cycle acceleration.

DESCRIPTION


The VM series models made entirely of AISI304 stainless steel, with digital control panel and standard absolute vacuum sensor, it is characterized by ease of use and compactness. Its versatility makes it possible to pack the products in the chamber, in external containers via the suction device and in embossed envelopes outside the chamber. Easy maintenance and cleaning make it a precise, fast, versatile and reliable work tool.

AVAILABLE OPTIONS

- 1) 2 x SHORT SEALING BAR
- 2) GAS+SOFTAIR:
inert gas injection with 2 nozzles and the "Gasplus" system, allowing up to 90% inert gas injection for highly crush-sensitive products and slow air return "Softair" included.
- 3) GAS+SOFTAIR+ MANUAL DEGAS:
In addition to the optional features in point 2, includes manual deaeration cycles.
- 4) SEAL CUTTING
- 5) OIL RECIRCULATION PUMP IS OPTIONAL IN THE 50/60HZ VERSION;

ACCESSORIES (NOT INCLUDED)

- Storage, cooking, and "cook&chill" bags; embossed bags;
- Inclined stainless steel shelf for liquid packaging;
- Stainless steel vacuum containers;
- External vacuum aspiration kit;




SEALING BAR 613mm
VACUUM PUMP 60 m³/h
ABSOLUTE SENSOR CONTROL



TECHNICAL DATA SHEET

CHAMBER VACUUM PACKAGING MACHINE

VM 62H OEM



TECHNICAL DATA

Length of seal L1	mm	613 (500)
Nominal pump speed	m³/h	60
Final pressure	mbar	2
Chamber size FxGxH	mm	535x650x200
Useful chamber space P	mm	422 (538)
Chamber depth L	mm	130
Chamber volume	Lt	70
Power	kW	1,5 – 2,4
Electrical voltage/Frequency/Phases	V/Hz	230-400V / 50Hz 3P+N+PE 16A 190-460V 50/60Hz 3P+N+PE 16A
Power cord and plug		4,5m / CEE
Housing materials		Steel inox (AISI304)
Vacuum chamber material		Steel inox (AISI304)
Lid material		PMMA (plexiglas)
Overall dimensions AxBxC	mm	771x700x1017
Maximum height with open lid C1	mm	1380
Distance between supports DxE	mm	/
Weight (with shelves)	kg	/
Noise level	dB(A)	<70
Environmental operating temperature (min-max)	°C	12-40